

Model: AE2430Z-FZ3C
Product Description

Type:	Reciprocating Compressors
Application:	LBP - Low Back Pressure
ProductDescription:	R-404A
Voltage/Frequency:	220-240V ~ 50Hz
Version:	N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE	200V ~ 50HZ	2700	680	791	587	4.6	1.16	1.35	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	45°C (113°F)
ASHRAE	240V ~ 50HZ	2700	680	791	631	4.28	1.08	1.35	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	45°C (113°F)

General

Evaporating Temp. Range:	-40°C to -10°C (-40°F to 14°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	12
Weight Unit of Measure:	KG
Displacement (cc):	14.51
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	386.65

Electrical

Voltage Range (50 Hz):	198-253
Voltage Range (60 Hz):	
Locked Rotor Amps (LRA):	21.5
Rated Load Amps (RLA 50 Hz):	3.52
Rated Load Amps (RLA 60 Hz):	0
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	3.37
Motor Resistance (Ohm) - Start:	11.99
Motor Type:	CSR
Overload Type:	
Relay Type:	

Agency Approval

CCC Listed, CE Listed, IRAM Listed, TIS Listed