

Designation	<b>NJ2192GK</b>
Nominal Voltage/Frequency	<b>220-240 V 50 Hz</b>
Engineering Number	<b>944AA01</b>

**A - APPLICATION / LIMIT WORKING CONDITIONS**

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm <sup>2</sup> ] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm <sup>2</sup> ] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

**B - MECHANICAL DATA**

1 Commercial designation	11/4	[hp]
2 Displacement	26.11	[cm <sup>3</sup> ] (1.593 cu.in)
2.1 Bore	41.770	
2.2 Stroke	9.533	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight(with oil charge)	20.35	[kg] (44.86 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

**C - ELECTRICAL DATA**

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device		
3 Start capacitor	88-108(330)	[µf(VAC minimum)]
4 Run capacitor	20(440)	[µf(VAC minimum)]
5 Motor protection (external)	15HM2459-168	
6 Start winding resistance	11.20	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.90	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ	

**D - PERFORMANCE - CHECK POINT DATA**

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
3842	968	1126	854	4.00	26.05	4.50	1.13	1.32	

**E - PERFORMANCE - CURVES**

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1758	443	515	503	2.34	11.82	3.48	0.88	1.02
-35	(-31)	2438	614	714	591	2.73	16.44	4.15	1.04	1.21
-30	(-22)	3286	828	963	682	3.13	22.23	4.84	1.22	1.42
-25	(-13)	4308	1086	1262	775	3.55	29.27	5.56	1.40	1.63
-20	(- 4)	5506	1388	1613	870	3.99	37.61	6.31	1.59	1.85
-15	(+ 5)	6886	1735	2018	967	4.44	47.32	7.11	1.79	2.08
-10	(+14)	8451	2130	2476	1065	4.92	58.46	7.95	2.00	2.33

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1412	356	414	482	2.21	9.47	2.92	0.74	0.86
-35	(-31)	2095	528	614	586	2.68	14.10	3.58	0.90	1.05
-30	(-22)	2920	736	856	692	3.17	19.71	4.22	1.06	1.24
-25	(-13)	3890	980	1140	802	3.68	26.38	4.86	1.22	1.42
-20	(- 4)	5011	1263	1468	914	4.21	34.15	5.48	1.38	1.61
-15	(+ 5)	6287	1584	1842	1028	4.76	43.11	6.11	1.54	1.79
-10	(+14)	7721	1946	2262	1144	5.35	53.31	6.75	1.70	1.98

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1050	265	308	436	2.01	7.03	2.43	0.61	0.71
-35	(-31)	1761	444	516	562	2.58	11.84	3.11	0.78	0.91
-30	(-22)	2587	652	758	692	3.18	17.44	3.72	0.94	1.09
-25	(-13)	3532	890	1035	824	3.80	23.90	4.29	1.08	1.26
-20	(- 4)	4600	1159	1348	960	4.44	31.29	4.81	1.21	1.41
-15	(+ 5)	5796	1461	1698	1098	5.12	39.66	5.29	1.33	1.55
-10	(+14)	7124	1795	2087	1238	5.83	49.09	5.74	1.45	1.68

**F - EXTERNAL CHARACTERISTICS**

1 Base plate	American Standard
2 Tray holder	No
3 Connectors	
3.1 SUCTION	9.6 +0.07/+0.00 [mm] (0.378" +0.003"/+0.000")
3.1.1 Material	Copper
3.1.2 Shape	Vertical
3.2 DISCHARGE	8 +0.07/+0.00 [mm] (0.315" +0.003"/+0.000")
3.2.1 Material	Copper
3.2.2 Shape	Slanted J
3.3 PROCESS	9.6 +0.07/+0.00 [mm] (0.378" +0.003"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Vertical
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs