

AIR COOLERS SBDC 035 - 4 POLES

Modello Model	Potenza Capacity		Portata aria Air flow	Superficie Surface	Freccia aria Air throw	Livello press. sonora (5m) Noise pressure level (5 m)	Ventilatori Fans		Sbrinamento elettrico Electric defrost	Connex. Connections		Volume tubi Tubes volume	Peso Weight
	SC1, R404A, Tair=10°C, DT1=10K	SC2, R404A, Tair=0°C, DT1=8K					N x D	Caratteristiche Features		Ingresso Inlet	Uscita Outlet		
	kW	kW	m3/h	m2	m	dB(A)	mm	1ph/230V/50Hz	W	mm	mm	dm3	kg

4 mm - Passo alette , Fin spacing

SBDC035/1 B4_4S	4,8	3,3	2600	12,2	10	52	1x350	130W - 0,58A - 1400 1/min	1100	12	16	1,3	33
SBDC035/1 C4_4S	6,0	4,1	2450	16,2	10	52	1x350		1100	12	16	1,8	34
SBDC035/2 B4_4S	10,5	7,2	5200	25,2	10	55	2x350		2260	12	16	2,7	50
SBDC035/2 C4_4S	12,4	8,8	4950	33,6	10	55	2x350		2260	12	16	3,6	53
SBDC035/3 B4_4S	15,1	10,5	7850	38,3	11	56	3x350		3460	12	16	4,1	67
SBDC035/3 C4_4S	16,7	12,0	7450	51,0	11	56	3x350		3460	12	16	5,5	73
SBDC035/4 B4_4S	18,1	12,8	10500	51,3	11	57	4x350		4660	12	16	5,6	88
SBDC035/4 C4_4S	25,3	17,9	9950	68,4	11	57	4x350		4660	12	16	7,4	95

6 mm - Passo alette , Fin spacing

SBDC035/1 B6_4S	3,5	2,5	2700	8,3	10	52	1x350	130W - 0,58A - 1400 1/min	1100	12	16	1,3	32
SBDC035/1 C6_4S	4,8	3,2	2550	11,1	10	52	1x350		1100	12	16	1,8	33
SBDC035/2 B6_4S	8,2	5,6	5400	17,2	10	55	2x350		2260	12	16	2,7	48
SBDC035/2 C6_4S	10,1	7,0	5200	23,0	10	55	2x350		2260	12	16	3,6	51
SBDC035/3 B6_4S	12,2	8,5	8150	26,2	11	56	3x350		3460	12	16	4,1	64
SBDC035/3 C6_4S	14,2	9,9	7800	34,9	11	56	3x350		3460	12	16	5,5	68
SBDC035/4 B6_4S	15,2	10,7	10850	35,1	11	57	4x350		4660	12	16	5,6	84
SBDC035/4 C6_4S	20,7	14,2	10400	46,8	11	57	4x350		4660	12	16	7,4	89

8 mm - Passo alette , Fin spacing

SBDC035/1 B8_4S	2,1	2,9	2750	6,4	10	52	1x350	130W - 0,58A - 1400 1/min	1100	12	16	1,3	31
SBDC035/1 C8_4S	2,7	4,0	2650	8,5	10	52	1x350		1100	12	16	1,8	32
SBDC035/2 B8_4S	4,7	6,6	5500	13,3	10	55	2x350		2260	12	16	2,7	47
SBDC035/2 C8_4S	5,9	8,6	5300	17,7	10	55	2x350		2260	12	16	3,6	49
SBDC035/3 B8_4S	7,1	10,4	8300	20,1	11	56	3x350		3460	12	16	4,1	63
SBDC035/3 C8_4S	8,6	12,4	8000	26,8	11	56	3x350		3460	12	16	5,5	66
SBDC035/4 B8_4S	9,2	13,2	11050	27,0	11	57	4x350		4660	12	16	5,6	82
SBDC035/4 C8_4S	12,0	17,5	10650	36,0	11	57	4x350		4660	12	16	7,4	86

Livello pressione sonora in campo libero secondo ISO 3744
Noise pressure level in freefield according to ISO 3744