

|                  |  |                              |           |                   |             |
|------------------|--|------------------------------|-----------|-------------------|-------------|
|                  | Unit model   |                              |           | TWV1003137        |             |
|                  | Compressor   |                              |           | TAJ9510Z          |             |
|                  | Power supply   |                              | [V/ph/Hz] | 400/3/50          |             |
|                  | Refrigerant  |                              |           | R452A/R448A/R449A |             |
|                  | Dimensions   | width                        | [mm]      | 390               |             |
|                  |  | depth                        | [mm]      | 480               |             |
|                  |  | height                       | [mm]      | 360               |             |
|                  | Accessories  | water pressostatic valve     |           |                   | AWR1203     |
|                  |  | liquid receiver              |           |                   | 4,6 L       |
|                  |  | cooling fan                  |           |                   | Ø 200       |
|                  |  | tube in tube water condenser |           |                   | CHS3/S-P    |
|                  |  | double pressure switch       |           |                   | PS15AAL-S01 |
|                  | Connections  | high pressure relief device  |           |                   | yes         |
|                  |  | liquid                       | [Ø]       |                   | 10          |
|                  |  | suction                      | [Ø]       |                   | 16          |
|                  |  | water                        | [Ø]       |                   | 3/8"        |
| UNIT PERFORMANCE | I MAX  |                              | [A]       | 2,38              |             |
|                  | P MAX  |                              | [W]       | 1220              |             |
|                  | T-in water   |                              | [°C]      | 15                |             |
|                  | T-cond   |                              | [°C]      | 35                |             |
|                  | cooling capacity T <sub>evap</sub> =-10°C +35°C cond EN12900 | R452A                        |           | [W]               | 1720        |
|                  | cooling capacity T <sub>evap</sub> =-10°C +35°C cond EN12900 | R448A / R449A                |           | [W]               | 1612        |

compressor  
 basement in galvanized metal sheet  
 tube-in-tube water condenser  
 compressor cooling fan  
 double pressure switch  
 liquid receiver (with safety valve on larger models)  
 liquid and suction valve  
 2 m power cable for single-phase models  
 empty and not wired box for three-phase models  
 pressostatic water valve

