

	Unit model			TWV1103137	
	Compressor			TAJ9513Z	
	Power supply		[V/ph/Hz]	400/3/50	
	Refrigerant			R452A/R448A/R449A	
	Dimensions	width	[mm]	390	
		depth	[mm]	480	
		height	[mm]	360	
	Accessories	water pressostatic valve			AWR1203
		liquid receiver			4,6 L
		cooling fan			Ø 200
		tube in tube water condenser			CHS3/S-P
		double pressure switch			PS15AAL-S01
	Connections	high pressure relief device			yes
		liquid	[Ø]		10
		suction	[Ø]		16
		water	[Ø]		3/8"
UNIT PERFORMANCE	I MAX		[A]	2,45	
	P MAX		[W]	1470	
	T-in water		[°C]	15	
	T-cond		[°C]	35	
	cooling capacity Tevap=-10°C +35°C cond EN12900	R452A		[W]	2125
	cooling capacity Tevap=-10°C +35°C cond EN12900	R448A / R449A		[W]	1991

compressor
basement in galvanized metal sheet
tube-in-tube water condenser
compressor cooling fan
double pressure switch
liquid receiver (with safety valve on larger models)
liquid and suction valve
2 m power cable for single-phase models
empty and not wired box for three-phase models
pressostatic water valve

