

	Unit model			WV3813137	
	Compressor			AE2425Z	
	Power supply		[V/ph/Hz]	230/1/50	
	Refrigerant			R452A/R448A/R449A	
	Dimensions	width	[mm]	300	
		depth	[mm]	510	
		height	[mm]	250	
	Accessories	water pressostatic valve			AWR1203
		liquid receiver			1,4 L
		cooling fan			Ø 200
		tube in tube water condenser			CHS1/S
		double pressure switch			PS15AAL-S01
	Connections	high pressure relief device			no
		liquid	[Ø]		6
		suction	[Ø]		10
	UNIT PERFORMANCE		water	[Ø]	3/8"
I MAX			[A]	3,15	
P MAX			[W]	660	
T-in water			[°C]	15	
T-cond			[°C]	35	
cooling capacity T <sub>evap</sub> =-30°C +35°C cond EN12900		R452A	[W]		447
cooling capacity T <sub>evap</sub> =-30°C +35°C cond EN12900		R448A / R449A	[W]		429

compressor  
 basement in galvanized metal sheet  
 tube-in-tube water condenser  
 compressor cooling fan  
 double pressure switch  
 liquid receiver (with safety valve on larger models)  
 liquid and suction valve  
 2 m power cable for single-phase models  
 empty and not wired box for three-phase models  
 pressostatic water valve

