

	Unit model			WV5811137	
	Compressor			CAJ4476Y	
	Power supply		[V/ph/Hz]	230/1/50	
	Refrigerant			R134a/R513A	
	Dimensions	width	[mm]	390	
		depth	[mm]	480	
		height	[mm]	360	
	Accessories	water pressostatic valve			AWR1203
		liquid receiver			4,6 L
		cooling fan			Ø 200
		tube in tube water condenser			CHS3/S-P
		double pressure switch			PS15AAL-S01
	Connections	high pressure relief device			yes
		liquid	[Ø]		10
suction		[Ø]		12	
	water	[Ø]		3/8"	
UNIT PERFORMANCE	I MAX		[A]	5,71	
	P MAX		[W]	873	
	T-in water		[°C]	15	
	T-cond		[°C]	35	
	cooling capacity Tevap=-10°C +35°C cond EN12900	R134a		[W]	1085
	cooling capacity Tevap=-10°C +35°C cond EN12900	R513A		[W]	1165

compressor
basement in galvanized metal sheet
tube-in-tube water condenser
compressor cooling fan
double pressure switch
liquid receiver (with safety valve on larger models)
liquid and suction valve
2 m power cable for single-phase models
empty and not wired box for three-phase models
pressostatic water valve

