

# VRR36C4

## Recovery Unit

# 4-Cylinder

Suit for  
**R32**



Oil-Free Compressors



3 High-Speed Cooling Fans



Digital Backlit Display



Purge Function



Brushless DC Technology

## Fastest · Most Powerful

### 4-Cylinder

- More powerful

### Super-Efficient Condenser

- Over-sized micro-channel condenser
- 3 cooling fans

### Brushless DC Motor

- More efficient

### Large Digital Display

- Easy-to-read large LCD display
- Backlit for clarity

### Dual Oil-Free Compressors

- Suitable for all commonly used refrigerants

Model	VRR36C4			
Refrigerant	Categorys III : R12, R134a, R401C, R500, 1234yf Categorys IV : R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 Categorys V : R402A, R404A, R407A, R407B, R410A, R507, R32			
Power Supply	220-240V~50/60Hz	115V~/60Hz		
Motor	Brushless DC motor 1.5HP			
Motor Speed	3000 rpm			
Maximal Current Draw	8.5 A	12 A		
Compressor	Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off	38.5bar/3850kPa(558psi)			
Recovery Rate (kg/min)	R134a III	R22 IV	R410A V	
	High Temp Vapor(40°C)	0.75	0.94	0.95
	Vapor	0.60	0.80	0.85
	Liquid	4.00	4.50	4.65
	Push/pull	8.60	9.80	11.0
Operating Temperature	0 °C -40 °C			
Dimensions	410×275×300 mm			
Weight	19 kg			